

YTO - 240P

	Model	YTO-240P
Main Dimension of tractor	rated output	19.12kw (26hp)
	type	4X2
	model of engine	ZH1115E2
	rated traction(N)	4900
	overall dimension(L*W*H)	2700*1250*1335(to steering wheel)
	wheel base(mm)	1400
	front wheel tread(mm)	900
	rear wheel tread(mm)	1020
	min.ground clearance(mm)	320
	min turning diameter	2800
	Weight	min-usage mass
	model of front axle	nonadjustable
speed	no. of gearshift	front 8 rear 2
	theoretical speed range(km/h)	3.17-32.7/4.2-11.8
	pump position	side
	displacement(l/mn)	8.1
	max lifting capacity(Kn@610mm)	4
工作装置working device	type	rear 3-point links, cat O
	depth for the implement control	floating
	PTO shaft	model 135, 540r/min
Engine	model	ZH1115E2
	type	4 single cylinder,horizontal, 4-strokes,direc injection
	bore*stroke(mm)	115X115
	rated rotary speeded(r/min)	2200
	rated power(kw)	19.12
	max torque(N.m)	78.61
	max torque rotary speed(r/min)	1760
	fuel consumption ratio(g/kw.h)	242
	cooling type	water cooling, circulation
Configuration		5.0-16/9.5-24, PTO electric start,China-II emission engine, tire 5.0-16/9.5-24,rear PTO,gear pump,hydraulic system