AGRI MASTER 604 SPECIFICATIONS

ENGINE		РТО		Dimensions & Weights	
Brand and model	YT4A2-T89S-1	Type and Shaft teeth	splines SIX	Min Operation weight (KGs)	2198
Cylinders	4 cylinders	Rotation speed (rpm)	540/1000	Overall dimension L×W×H(mm)	3990*1810*2590
Туре	Verticle & water-cooled	PTO shaft power (Kw)	41.5	Front Axle	4WD
Technology	China-II			Ground clearance (mm)	380
Power动力	44.1 KW / 60HP / 4156CC	Speed range		Min turning radius (m)	3.9
Crankshaft Rated speed (rpm)	2200	Forward (km/h)	FROM 2.27 TO 31.94	Wheel Tread Front (mm)	1300
Maximum Torque N.m.	262	Reverse (km/h)	FROM 1.72 TO 24.16	Wheel Tread Rear (mm)	1315
Max traction force (KN)	14.7				
Engine Bore (mm)	105	Hydraulic System		Tyres	
Engine Stroke (mm)	120	Lifting capacity at lift point	KG 1520	Front	9.5-24
Fuel usage g/(kW.h)	260	Maximum Pressure Mpa	18	Rear	14.9-30
Fuel Tank Capacity (L)	99.4	Pump Capacity, L/Min	14		
Gearbox		Transmission + Hydraulic O	il, L 42	General Information	
Gearshift type	sleeve	3-Position System Force	e, Position & Draft	Steering wheel	bydraulic
F+R No. of gearshift	8+8			Steering Type	standard
				Canopy	Included
Clutch				Hitch	Included
Size	11			Front Weights (KGS)	120
Туре	dry			Rear Werights (KGs)	320
				Seat	Elastic