## <u>AGRI MASTER - 804</u> <u>SPECIFICATIONS</u>

ENGINE		РТО		Dimensions & Weights	
Brand and model	YTO-LR4B5-23	Type and Shaft teeth	splines six	Min Operation weight (KGs)	3215
Cylinders	4 cylinders	Rotation speed (rpm)	540/1000	Overall dimension L×W×H(mm)	4085*1929*2568
Туре	Verticle & water-cooled	PTO shaft power (Kw)	53.1	Front Axle	4WD
Technology	China-II			Ground clearance (mm)	340
Power	59 KW / 80HP / 4947CC	Speed range		Min turning radius (m)	4.3
Crankshaft Rated speed (rpm)	2300	Forward (km/h)	from 3.22 to 33.09	Wheel Tread Front (mm)	1350~1650
Maximum Torque N.m.	306	Reverse (km/h)	3.64, 13.12	Wheel Tread Rear (mm)	1510 <b>~</b> 1790
Max traction force (KN)	15				
Engine Bore (mm)	108	Hydraulic System		Tyres	
Engine Stroke (mm)	135	Lifting capacity at lift poi	nt KG 2215- 2825	Front	9.5-24
Fuel usage g/(kW.h)	240	Maximum Pressure Mpa	18	Rear	16.9-30
Fuel Tank Capacity (L)	78	Pump Capacity, L/Min	36		
Gearbox		Transmission + Hydraulic Oil, L 61		General Information	
Gearshift type	sleeve	3-Position Fo	orce, Position & Draft	Steering wheel	Hydraulic
F+R No. of gearshift	16+4			Steering Type	standard
				Canopy	Included
Clutch				Hitch	Included
Size	12 inch			Front Weights (KGs)	180
Туре	dry			Rear Werights (KGs)	360
				Seat	Elastic